

UNITED STATES PATENT AND TRADEMARK OFFICE

Cer

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/765,487	01/27/2004	Mario Boisvert	14-733C2D1	9537
28060 7590 10/31/2007 TAROLLI, SUNDHELM, COVELL & TUMMINO, LLP 1300 EAST NINTH STREET			EXAMINER	
			FLETCHER, MARLON T	
	SUITE 1700 CLEVELAND, OH 44114			PAPÉR NUMBER
	•		2837	
			MAIL DATE	DELIVERY MODE
			10/31/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
	10/765,487	BOISVERT ET AL.				
Office Action Summary	Examiner	Art Unit				
	Marlon T. Fletcher	2837				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply be timwill apply and will expire SIX (6) MONTHS from e, cause the application to become ABANDONE	l. nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 20 J	<u>une 2007</u> .					
2a) This action is FINAL . 2b) ⊠ This	This action is FINAL . 2b)⊠ This action is non-final.					
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) <u>1-37</u> is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) Claim(s) is/are allowed. 6) Claim(s) <u>1-37</u> is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/o	wn from consideration.					
Application Papers						
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) acc Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine	cepted or b) objected to by the lead rawing(s) be held in abeyance. Section is required if the drawing(s) is objection.	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 						
	,					
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ate				

10/765,487 Art Unit: 2837

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 2. Claims 1-23 and 28-35 are rejected under 35 U.S.C. 102(b) as being anticipated by Okuyama et al. (4,608,637)

As recited in claims 1 and 2, Okuyama et al. disclose an apparatus for controlling motion of a motor driven element over a range of motion and for altering said motion when undesirable resistance to the motion is encountered, said apparatus comprising: a sensor (6a, 6ab, 6d, 6da) for measuring a parameter of a motor coupled to the motor driven element that varies in response to a resistance to motion during all or part of a range of motion of the motor driven element (column 7, lines 49-62); a memory for storing a number of measurement values from the sensor based on measurements of said parameter over at least a portion of the range of motion (column 8, line 51-64); a controller (microcomputer 9) coupled to the memory for determining to de-activate the motor based on the measurement values stored in the memory as the motor driven element moves over its range of motion; and a controller interface coupled to the motor (Ma, Md, Mab, Mda) for altering motion of said motor driven element in response to a

10/765,487 Art Unit: 2837

determination made by the controller (column 5, lines 9-60), wherein altering is also in response to a determination that the parameter is outside the parameter range.

As recited in claims 3 and 31, Jones et al. disclose the method, wherein the motor driven element is a window or panel and additionally comprising reverse actuating the window or panel prior to moving said window or panel in a direction to close the window or panel (column 6, lines 24-33).

As recited in claim 4, Jones et al. disclose the method, additionally comprising maintaining a position of the window or panel based on the sensed parameter and the reverse actuation is initiated if a leading edge of the window or panel is near a closed position (column 6, lines 24-33).

As recited in claims 5, 10, and 11, Jones et al. disclose the method, movement is first initiated toward a closed position when a leading edge of the window or panel is near the closed position and wherein the reverse actuation is performed upon a sensing of an obstacle that is based on determining the parameter is outside the parameter range (column 7, lines 49-62).

As recited in claims 6 and 33, Jones et al. disclose an apparatus for controlling activation of a motor coupled to a motor vehicle window or panel for moving said. window or panel along a travel path and deactivating the motor if an obstacle is encountered by the window or panel, said apparatus comprising: a sensor for sensing movement of the window or panel and providing a sensor output signal related to a speed of movement of the window or panel (discussed above; column 7, lines 30-37), and a controller having an interface coupled to the sensor and the switch for controllably

10/765,487

Art Unit: 2837

energizing the motor (figure 4a); said controller sensing a collision with an obstruction when power is applied to the controller by: monitoring movement of the window or panel by monitoring a signal from the sensor related to the movement of the window or panel (column 7, lines 6-23; and column 8, lines 35-50), identifying a collision of the window or panel with an obstacle due to a change in the signal from the sensor that is related to a change in movement of the window or panel (Abstract; and column 8, lines 51-64); and outputting a control signal to said switch to deactivate said motor in response to a sensing of a collision between an obstacle and said window or panel (column 8, line 65 – column 9, line 7).

As recited in claims 7, 29, and 35, Jones et al. disclose the apparatus, wherein the controller comprises a programmable controller including a processing unit for executing a control program and including a memory for storing multiple window or panel speed values corresponding to a signal received from the sensor (column 6, lines 52-60).

As recited in claims 8 and 30, Jones et al. disclose the apparatus, additionally comprising one or more limit switches (11) for use by the controller to determine window or panel position for use in identifying a collision.

As recited in claim 9, Jones et al. disclose the apparatus, wherein the control program adjusts an obstacle detection threshold in real time based on immediate past measures of the signal sensed by the sensor to adapt to varying conditions encountered during operation of the window or panel (column 8, lines 65 – column 9, line 7).

As recited in claims 12, 19, 20, and 28, Jones et al. disclose apparatus for

10/765,487 Art Unit: 2837

controlling activation of a motor for moving an object along a travel path and deactivating the motor if an obstacle is encountered by the object comprising: a) a movement sensor for monitoring movement of the object as the motor moves said object along a travel path (discussed above; a switch for controlling energization of the motor with an energization signal (column 6, lines 52-60); and a controller (microcomputer 9) including an interface coupled to the switch means for controllably energizing the motor and said interface additionally coupling the controller to the movement sensor for monitoring signals from said movement sensor (discussed above; said controller comprising a stored program that: determines motor speed from an output signal from the movement sensor; calculates an obstacle detect threshold based on motor speed of movement detected during at least one prior period of motor operation (column 7, lines 6-36); compares a value based on currently sensed motor movement with the obstacle detect threshold; and outputs a signal from the interface to said switch for stopping the motor if the comparison based on currently sensed motor movement indicates the object has contacted an obstacle.

As recited in claim 13, Jones et al. disclose the apparatus, wherein the controller includes a buffer memory for storing successive values of motor movement for use in determining the obstacle detect threshold (column 8, lines 51-53).

As recited in claim 14, Jones et al. disclose the apparatus, wherein the controller includes a clock and an input from the movement sensor is in a form of a sequence of pulses and further wherein the controller counts clock signals occurrences between receipt of pulses to provide an indication of motor speed (column 7, lines 30-37).

10/765,487 Art Unit: 2837

As recited in claim 15, Jones et al. disclose the apparatus, wherein the controller includes an interface for monitoring user actuation of control inputs for controlling movement of the window or panel and wherein the controller maintains a motor energization sequence a specified minimum time period in response to a short period user actuation of said control inputs to maintain position accuracy in monitoring a window or panel movement (column 7, lines 49-62).

As recited in claim 16, Jones et al. disclose the apparatus, wherein the controller includes an interface for monitoring user actuation of control inputs for controlling movement of the object and wherein in response to a specified input the controller conducts a (calibration motor energization sequence to determine parameters of object (column 7, lines 6-29).

As recited in claims 17 and 32, Jones et al. disclose the apparatus, wherein the motor is coupled to a motor vehicle window or panel and wherein the controller includes an interface for monitoring user actuation of control inputs for controlling movement of the window or panel and wherein the controller maintains a position indication which is updated in response movement of the window or panel and further wherein the controller reverse actuations the motor near an end point in an object path of travel to avoid false obstacle detection in the region of closure of the window or panel.

As recited in claim 18, Jones et al. disclose the apparatus, wherein the sensor is a current sensor and wherein the controller includes means for adjusting the obstacle threshold based on dynamic motor current as sensed from the current sensor to take into account varying loads experienced by the motor (inherent via discussion above).

10/765,487 Art Unit: 2837

With respect to claims 21, 22, and 34, Okuyama et al. a Hall-effect sensor (6a-) and a magnetic pick-up (7a-).

As recited in claim 23, Jones et al. disclose the apparatus, additionally comprising an obstacle detector having an output coupled to the controller that senses a disruption in a region through which the window or panel moves (discussed above).

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claim 24-27, 36, and 37, are rejected under 35 U.S.C. 103(a) as being unpatentable over Okuyama et al.

As recited in claim 24-27, Okuyama et al. do not disclose the apparatus, wherein the obstacle detector comprises an infrared light source and detector .

However, Official Notice is taken with respect to infrared light sources being well known in the art to detect movement of an object.

10/765.487

Art Unit: 2837

It would be obvious to use any type of sensor, because the teachings merely provide alternate means for providing the same, wherein one could substitute one sensor or detector for another.

With respect to claims 36 and 37, Okuyama et al. disclose the claimed invention except for the range in which the measurements are taken (40 milliseconds). It would have been obvious to one having ordinary skill in the art at the time the invention was made to provide measurements at forty millisecond interval, since it has been held that where the general conditions of a claim are disclosed in the prior art, discovering the optimum or workable ranges involves only routine skill in the art. In re Aller, 105 USPQ 233.

Response to Arguments

Applicant's arguments with respect to claims 1-37 have been considered but are moot in view of the new ground(s) of rejection.

The applicant argued that Wrenbeck et al. were not prior art. The examiner agrees. However, this required further search. The search reveal another reference which better read on the claims. The claims are rejected based on the newly cited reference.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Marlon T. Fletcher whose telephone number is 571-272-2063. The examiner can normally be reached on M-F.

10/765,487 Art Unit: 2837

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Lincoln Donovan can be reached on 571-272-1988. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MTF 10/25/2007

Primary Examiner